

Scrubber opal 80



Walk-behind
machine with
traction



Power supply
24V/210Ah



Theoretical hourly
performance 3-5h



Cleaning width
785mm



Solution/recovery
tanks 75/85l



Disc brush
2x406mm



Brushes
pressure max.
50kg



Brush speed
160rpm



OPTIONAL



Lithium batteries




3S - Solution
saving system



Ozono system

Robust and efficient, the **Opal 80 scrubber dryer** is the ideal solution for those who require **high performance** and **maximum autonomy**. Its **large tank capacity** and advanced technology make it perfect for tackling **wide areas** while delivering consistently excellent results. Reliable and powerful, it ensures spotless floors with minimal effort.



TECHNICAL DATA

Manufacturer: Floorpul NV
Registered Office: Generaal Deprezstraat 10A
 8530 Harelbeke
 West-Vlaanderen - Belgium

Theoretical productivity:	3140 m²/h
Squeegee width:	1000 mm
Brush motor:	2x 350 Watt
Traction motor:	300 Watt
Maximum gradient:	10%
Forward speed:	4 km/h
Suction motor:	570 Watt
Suction vacuum:	160 mbar
Machine dimensions:	L: 1525 mm
	(w/o squeegee) W: 855 mm
	H: 1045 mm
Machine weight (w/o batteries)	158 kg
Battery compartment:	L: 500 mm
	W: 385 mm
	H: 290 mm
Class:	III
Protection level:	IP X3

WELLBEING and COMFORT FOR THE OPERATOR



Sound pressure level L_{pa}
 (in accordance with annex DD IEC/EN 60335-2-72)

75.3 db (A)



Sound pressure level:
 in SILENT mode

68.9 db (A)

Hand-arm vibration level
 (in accordance with annex EE IEC/EN 60335-2-72)

1.14 m/s²

DECLARATIONS



Machinery compliant with the safety and quality standards required by current European legislation and supplied with an EC Declaration of Conformity.



Machinery compliant with Regulation (EC) No. 1907/2006 (REACH) on the Registration, Evaluation, Authorisation and Restriction of Chemicals.



Machinery made with components that comply with Directive 2011/65/EU and 2015/863 (RoHS), which restricts the use of hazardous substances in electrical and electronic equipment.