

RUBY 55BT – 55BT PLUS



Walk behind machine with traction



Battery autonomy
2 - 4 h



Operating tension
24 V / 118 Ah/5H



Cleaning width
550 mm



Solution tank / recovery tank
40 / 45 l



Disc brushes
2 x 285 mm



Brushes pressure adjustable
max. 24,5 kg



Brushes speed
280 rpm



Theoretical working capacity:

2200 m²/h

Scrubber dryer with traction, modern design, robust, reliable and easy to use. Working width of 55cm. It is equipped with large diameter wheels (175mm) anti-skid and not marking, a parabolic squeegee, a large suction filter and a digital display. Tanks in ABS. The dirty water tank is removable without tools. The two models differ from the presence of an incorporated charger.

Strong Points:

- Battery autonomy
- Adjustable brush pressure
- Traction motor
- Tanks capacity
- Possibility to have an integrated charger (version Plus)

Water consumption :

Because of the strong mechanical action of the 2 brushes and the electrical valve we can limit the consumption of water and detergent :

Working position opening 1/4 = 0.362 L/min

Tap complete open = 1,45 L/min

Average water consumption per m² = 0,0527 l

With the full tank you can work between 30 and 110 min.

Technical data

| | |
|--------------------------------|--------------|
| Squeegee width | 770mm |
| Brushes motor | 420 Watt |
| Type of drive | automatic |
| Maximum gradient | 2% |
| Suction motor | 570 Watt |
| Suction vacuum | 120 mbar |
| Machine dimensions | |
| length | 1140 mm |
| height | 1053 mm |
| width without squeegee | 586 mm |
| Machine weight without battery | 84kg - 89kg |
| Traction motor | 120W |
| Movement speed | 4 km/u |
| Battery compartment | |
| length | 342 mm |
| width | 350 mm |
| height | 300 mm |
| Class | |
| Protection level | IP 23 |
| Noise level | <67,6 dB (A) |

