

ruby 55 / 55t



Theoretical working capacity: 1925 / 2200 m²/h

Floor cleaning machine, battery-driven, with brushes base group of 55 cm.



TECHNICAL DATA



Walk behind machine with or without traction



Power supply
24V/110Ah



Cleaning width
550mm



Brushes pressure adjustable
max.24,5kg



Battery autonomy 2-4h



Solution tank / recovery tank
40/45 l



Disc brushes
2x285mm



Brushes speed
280rpm

- Squeegee width:	770 mm
- Brushes motor:	420 Watt
- Motion system:	55: semiautomatic 55t: automatic
- Maximum gradient:	2%
- Suction motor:	570 Watt
- Suction vacuum:	120 mbar
- Machine dimensions:	L: 1140 mm W: 586 mm H: 1053 mm
- Machine weight w/o battery:	55: 74 kg 55t: 84 kg
- Traction motor 55t:	120 Watt
- Movement speed 55t:	4 km/h
- Battery compartment:	L: 350 mm W: 342 mm H: 295 mm
- Class:	III
- Protection level:	IP 23
- Loudness:	55: 66.2 dB (A) 55t: 67.6 dB (A)

It is a floor cleaning machine provided with a two counterrotating brushes brush base with a cleaning width of di 55 cm. The two models differ from each other for the presence of the electric traction system. The weight applied on the brushes is adjustable by the operator depending on the type of floors to clean. In the traction version it is possible to adjust the brushes angle in order to have them also helping the traction. Thanks to its strong structure, the easy maintenance and the simple controls, working with Ruby becomes very simple having also a high cleaning quality.